


allinea



Leaders in parallel software development tools

Debugging at Scale

Discipline, Magic, Inspiration and Science

Mark O'Connor
mark@allinea.com

www.allinea.com

Schedule Today

- 09:00 You, me and a short introduction
- 10:00 Debugging by Discipline
- 10:30 Debugging by Magic
- 11:15 Debugging by Inspiration
- 12:00 *Lunch (or zen meditation, I guess)*
- 13:00 Debugging by Science
- 13:45 Visually-scalable Profiling
- 14:30 Q&A

The Allinea Environment

- A modern integrated environment for HPC developers
- Supporting the lifecycle of application development and improvement
 - Allinea DDT : Productively debug code
 - Allinea MAP : Enhance application performance
- Designed for productivity
 - Consistent easy to use tools
 - Enables effective HPC development
- Improve system usage
 - Fewer failed jobs
 - Higher application performance



Allinea environment

Fix software problems - fast

- **Graphical debugger designed for:**
 - C/C++, Fortran, MPI, CUDA, SHMEM, UPC
 - Multithreaded code
 - Single address space
 - Multiprocess code
 - Interdependent or independent processes
 - Accelerated codes
 - GPUs, Intel Xeon Phi
 - Any mix of the above
- **Slash your time to debug :**
 - Reproduces and triggers your bugs instantly
 - Helps you easily understand where issues come from quickly
 - Helps you to fix them as swiftly as possible





Leaders in parallel software development tools


Allinea MAP: a new kind of profiling

Get a quick, clear performance report


No need to instrument,
no need to recompile.

From one process to
tens of thousands.

20Mb output files,
5% slowdown.



Debugging by Discipline



Three techniques, rigorously applied, will dramatically improve your life.

At least, when it's time to debug.

Discipline 1: Logbook

```
$ mkdir logs  
$ vim logs/segfault-at-4096-procs
```

When running lu.E.4096 with the trace-4410.dat set, the job exited with: "An error occurred in MPI_Send [1i346-209:25319] on communicator MPI_COMM_WORLD MPI_ERR_RANK: invalid rank".

To reproduce: mpiexec -n 4096 lu.W.4096 trace-4410.dat on supermuc. Seems to happen every time.

- * Tried reading core file with gdb, "File truncated"
- * Set ulimit -c unlimited and ran again: ...

Exactly what happened, including error messages

How to reproduce it

Investigation notes

Discipline 2: Test script

1. Compile with debug information: `-g -O0`
2. Submit the job with the correct inputs
3. Wait for it to run...
4. Check the output for errors

So much can - and will - go wrong!

Instead, spend 2 minutes adapting an existing test script that does all of this and prints PASS or FAIL:

```
$ logs/segfault-at-4096-procs.sh  
Sep 27 15:29: Queued as job.43214  
Sep 27 18:01: Running...  
Sep 27 19:29: FAIL
```

Discipline 3: Source control

```
$ hg init
$ vim .hgignore
  syntax: glob
  *.o
  *~
  *.out
  *.err
$ hg status
$ hg add
$ hg commit -m "Switched to single-precision matrices"
```

You only need to know **four** or **five** commands:

\$ hg add main.c	Add a new file
\$ hg commit	Save the latest changes
\$ hg log	List all previous commits
\$ hg update 3	Update to commit #3
\$ hg revert	Abandon current changes

Source files

Input files

Test scripts

Executables

Output files

Summary: Discipline

Efficiency comes through preparation. Debugging a problem is much easier when you can:

- | | |
|-----------------------------------------|-----------------------|
| 1. Track what you've tried so far | Logbook |
| 2. Reproduce bugs with a single command | Test script |
| 3. Make and undo changes fearlessly | Source control |

When these are combined, **magical things** can happen...

Debugging by Magic




Any technology sufficiently advanced is indistinguishable from magic.

Unpredictable,
dangerous,
irresistible.

Favourite Magical Incantations

Program crashes:

```
$ ddt -n 512 -offline log.html myprog.exe arg1 arg2
```



00:25.325
0-255

Process stopped in main (hello.c:118) with signal SIGSEGV
Reason/Origin: tkill
Your program will probably be terminated if you continue.
You can use the stack controls to see what the process was


► Stacks

▼ Local variables for process 0 (ranges shown for 0-255)

Name	Value
argc	3
argv	0x7fffffff578 (from 0x7fffffff55)
beingWatched	32767
bigArray	
dest	-1429425880

Program deadlocks:

```
$ ddt -n 512 -start myprog.exe arg1 arg2
```



Favourite Magical Incantations

Suspected memory bugs:

```
$ ddt -n 512 myprog.exe arg1 arg2
```

☒ **Memory Debugging:** Balanced, No guard pages, Backtraces, Preload Details...

Heap Overflow/Underflow Detection

☒ Add guard pages to detect out of bounds heap access

Guard pages: 1 Add guard pages: After

The screenshot shows the Allinea DDT interface. On the left, a code editor displays the following C code:

```
45 }
46
47 void func3()
48 {
49     void* i = (void*) 1;
50     while(i++ || !i)
51         free((void*)i);
52 }
53
54 int main(int argc, char** argv)
55 {
```

In the center, a dialog box titled "Allinea DDT" displays the following message:

Processes 0-143:

Memory error detected in func3 (hello.c:51):

cannot locate pointer in heap

Buttons: Continue, Pause

On the right, the "Locals" pane shows the current line(s) and the value of the variable `i`:

Variable Name	Value
<code>i</code>	<code>0x2</code>

Protective Magic


Static analysis looks for common mistakes in code:

```
$ /path/to/ddt/libexec/cppcheck  
$ /path/to/ddt/libexec/ftnchek (not a typo!)
```

```
Checking cstartmpi.c...
```

```
[cstartmpi.c:172] (error) Memory leak: t2
```

Also integrated into DDT's GUI and on by default:



Disciplined Magic



A magical servant!

```
$ hg bisect --bad
```

"The current version has a problem"

```
$ hg bisect --good 4
```

"It worked back in version 4"

```
$ hg bisect -c logs/my-test.sh
```

Master, you broke it when you committed:
"Switched to single-precision matrices"

Summary: Magic

A good first step - can be a quick and easy way to fix:



Crashes



Deadlock



Memory
problems

Use source control and tests to create a magical servant:

```
$ hg bisect --bad  
$ hg bisect --good 4  
$ hg bisect -c logs/my-test.sh  
$ hg log -pr <changeset id>
```

Bonus - static analysis:
cppcheck / ftncheck

Debugging by Inspiration



Look at the problem,
see the solution.

Vertrauen ist gut,
trust your instincts.

Kontrolle ist besser,
test if they're right

Inspiration: Test your instincts

"Ah, I bet that's because `rl_x` is negative, so then the `y` offset will be wrong, and ..."

Check to see if you're right before changing the code:

```
$ ddt -n 64 -offline log.html -trace-at blas.c:412,rl_x myprog.exe
```

If your instinct is right, great! If it's wrong, **log it**:

```
$ cat >> logs/incorrect-y-merge
```

```
Hypothesis: Negative rl_x in blas.c:412 corrupts the y offset
```

```
Observation: according to -trace-at, rl_x = 4.113 in blas.c:412
```

Inspiration: Just look at the problem

Explore the data and program flow in an **interactive** session:

```
$ ddt -n 192 -start myprog.exe arg1 arg2
```

The screenshot displays the Allinea DDT debugger interface during a debugging session. The main window shows the source code of `linked.c` with the following code:

```
69 }
70
71 do {
72     struct llist* next = list->next;
73     value = list->value;
74     is_prime(value);
75     free(list);
76     list = next;
77 } while (list != NULL);
```

A yellow callout box points to line 72, stating: "On this line: 1 Process: rank 59".

The "Current Line(s)" window shows the variable `list` with a value of `0x7ffec9e07b8`.

The "DDT - Cross-Process Comparison View" window shows the expression `list > 0x0` and a table of process results:

Values	Process(es)	Statistics
0	59	Count:
1	0-58,60-95	

The "Current Group" window shows a list of processes:

Current Group	Processes	Paused	Playing	Finished
All	96 processes (0-95)	96	0	0
list > 0x0=0	59			
list > 0x0=1	95 processes (0-58,60-95)	95	0	0

The "Locals" window shows the following variables and their values:

Variable Name	Value
argc	1
argv	0x7ffffffcae8
next	0x7ffec9e07c8
rank	0
size	96
tv	{tv_sec = 1349083428,
value	35

The "Values logged" window shows the following values:

```
last: 0x0 primes->next: 0xc0c0ab1bc0c0ab1b value: from 29 to 89
```


Example: CUDA Dynamic Parallelism

```
__global__ void permute(int n, int *data) {
    __shared__ int smem[256];
    if (n <= 1)
        return;
    smem[threadIdx.x] = data[threadIdx.x];
    __syncthreads();
    smem[threadIdx.x] *= 2; // permute data in a trivial way
    __syncthreads();
    // Write back to GMEM since we can't pass SMEM to children.
    data[threadIdx.x] = smem[threadIdx.x];
    __syncthreads();
    if (threadIdx.x == 0) {
        permute<<< 1, 256 >>>(n/2, data);
        permute<<< 1, 256 >>>(n/2, data+n/2);
        cudaDeviceSynchronize();
    }
}
```

Debugging Dynamic Parallelism

```
int main(int argc, char** argv) {
    int input[256];
    int output[256];
    int *data;
    int i;

    for(i=0;i<256;++i)
        input[i] = 21;

    cudaMalloc(&data, 256 * sizeof(int));
    cudaMemcpy(data, input, 256 * sizeof(int), cudaMemcpyHostToDevice);
    permute<<< 1, 256 >>>(256, data);
    if (cudaSuccess != cudaGetLastError()) {
        return 1;
    }
    // wait for parent to complete
    if (cudaSuccess != cudaDeviceSynchronize()) {
        return 2;
    }
    cudaDeviceSynchronize();
    cudaMemcpy(output, data, 256 * sizeof(int), cudaMemcpyDeviceToHost);

    printf("output[42] = %d\n", output[42]);
    return 0;
}
```

Debugging Dynamic Parallelism

```
cuda/dynpar $ nvcc -g -G -00 -arch=sm_35 -rdc=true ./permute
.cu -o permute -lcudadevrt
cuda/dynpar $ ./permute
output[42] = 0
```



wait, what?

```
for (i=0; i<256; ++i)
    input[i] = 21;
```

```
cudaMalloc(&data, 256 * size)
cudaMemcpy(data, input, 256
```

```
smem[threadIdx.x] = data[threadIdx.x];
__syncthreads();
smem[threadIdx.x] *= 2; // permute data
__syncthreads();
// Write back to GMEM since we can't pass
data[threadIdx.x] = smem[threadIdx.x];
```

```
cuda/dynpar $ ddt ./permute
```




Application: /home/mark/allinea/tools/examples/dynamic_parallelism/p

Details

Application: me/mark/allinea/tools/examples/dynamic_parallelism/permute

Arguments:

☐ stdin file:

Working Directory:

☐ MPI

Details

☐ OpenMP

Details

☒ CUDA: Track allocations: disabled, Detect invalid accesses: enabled

Details

☐ Track GPU allocations (also enables CPU memory debugging)

☒ Detect invalid read/writes

☐ Memory Debugging

Details...

Environment Variables: none

Details

Plugins: none

Details

Run

Cancel

Select Tool:

Allinea DDT Trial Licence Expires 2013-11-11

Sales

Allinea MAP Support Expires 2013-11-11

Sales

Licence Serial Number: 4306 ?

[Support](#) [Tutorials](#) [allinea.com](#)

Allinea DDT v4-0-BRANCH cc74f8de8c46 Mar 13 2013

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K5

CUDA Threads (permute)

Block 0 0 0 Thread 254 0 0 Go Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

Application Code

- /
- Sources
 - permute-a.cu
 - main(int argc, char** arg
 - permute(int n, int *data)
- External Code

permute-a.cu

```
1 #include <stdio.h>
2
3 __global__ void permute(int n, int *data) {
4     __shared__ int smem[256];
5     if (n <= 1)
6         return;
7     smem[threadIdx.x] = data[threadIdx.x];
8     __syncthreads();
9     smem[threadIdx.x] *= 2; // permute data in a trivial way
10    __syncthreads();
11    // Write back to GMEM since we can't pass SMEM to children.
12    data[threadIdx.x] = smem[threadIdx.x];
13    __syncthreads();
14    if (threadIdx.x == 0) {
15        permute<<< 1, 256 >>>(n/2, data);
16        permute<<< 1, 256 >>>(n/2, data+n/2);
17        cudaDeviceSynchronize();
18    }
19 }
```

Locals Current Line(s) Current Stack

Current Line(s)

Variable Name	Value
data	0xb088c0008
smem	
threadIdx	{x = 254, y = 0,
threadIdx.x	254

Input/Output Breakpoints Watchpoints Stacks Kernel Progress View Tracepoints Tracepoint Output

Input/Output

Type here ('Enter' to send):

More

Ready

Program Stopped



Process 0:

Kernel 5 Thread <<<(0,0,0),(254,0,0)>>> stopped in
permute<<<(1,1,1),(256,1,1)>>> (permute-a.cu:7)
with signal CUDA_EXCEPTION_1 (Lane Illegal Address).

Reason/Origin: kill, sigsend or raise
Your program will probably be terminated if you
continue.
You can use the stack controls to see what the
process was doing at the time.

☒ Always show this window for signals

Continue

Pause


Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads: 1 2 K5 GPU

CUDA Threads (permute) Block 0 0 0 Thread 254 0 0 Go Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

Application Code
Sources
permute-a.cu
main(int argc, char** arg
permute(int n, int *data)
External Code

permute-a.cu

```

1  #include <stdio.h>
2
3  __global__ void permute(int n, int *data) {
4      __shared__ int smem[256];
5      if (n <= 1)
6          return;
7      smem[threadIdx.x] = data[threadIdx.x];
8      __syncthreads();
9      smem[threadIdx.x] *= 2; // permute data in a trivial way
10     __syncthreads();
11     // Write back to GMEM since we can't pass SMEM to children.
12     data[threadIdx.x] = smem[threadIdx.x];
13     __syncthreads();
14     if (threadIdx.x == 0) {
15         permute<<< 1, 256 >>>(n/2, data);
16         permute<<< 1, 256 >>>(n/2, data+n/2);
17         cudaDeviceSynchronize();
18     }
19 }

```

Locals Current Line(s) Current Stack

Locals

Variable Name	Value
data	0xb088c0008
n	2

Input/Output Breakpoints Watchpoints Stacks Kernel Progress View Tracepoints Tracepoint Output

Input/Output

Evaluate

Expression Value

data[threadIdx.x] 0
threadIdx {x = 254, y = 0, z = 0}

Type here ('Enter' to send):

More

Ready

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K5

CUDA Threads (permute)

Block

Project Files

Search (Ctrl+K)

Application Code

- /
- Sources
 - permute-a.cu
 - main(int argc, char** ar
 - permute(int n, int *data

External Code

Input/Output Breakpoints Watch

Input/Output

Type here ('Enter' to send):

More

Ready

Multi-Dimensional Array Viewer

Array Expression: data[\$i]

Evaluate

Distributed Array Dimensions: None

[How do I view distributed arrays?](#)

Cancel

Range of \$i

From:

0

To:

255

Display:

Rows

☒ Align Stack Frames☐ Auto-update☐ Only show if:[See Examples](#)

Data Table

Statistics

Goto

Visualize

Export

Full Window

i	0	5376
	1	5376
	2	5376
	3	5376
	4	5376
	5	5376
	6	5376
	7	5376
	8	5376
	9	5376
	10	5376
	11	5376

Help

Close

Locals Current Line(s) Current Stack

Locals

Variable Name	Value
data	0xb088c0008
n	2

Type: @generic int * @parameter

te

ession Value

a[threadIdx.x] 0

threadIdx {x = 254, y = 0, z = 0}

Multi-Dimensional Array Viewer

Array Expression:

Evaluate

Distributed Array Dimensions: [How do I view distributed arrays?](#)

Cancel

Range of \$i

From:

To:

Display:


☒ Align Stack Frames

☐ Auto-update

☒ Only show if: [See Examples](#)

Data Table

Statistics



Goto



Visualize



Export



Full Window

i	254	0
	255	0

Help

Close

Threads: 1 2 K5

Project Files   permute-a.cu 

Search (Ctrl+K) 

Sources

```

- [C] permut-a.cu
  [C] main(int argc, char** arg

```

External Code

```
1 #include <stdio.h>
```

```
3 __global__ void permute(int n, int *data) {
```

```
7 smem[threadIdx.x] = data[threadIdx.x];
8 syncthreads();
```

```
11 // Write back to GMEM since we can't pass SMEM to children.  
12 data[threadIdx.x] = smem[threadIdx.x];
```

```
14     if (threadidx % 2 == 0) {
15         permute<<< 1, 256 >>>(n/2, data);
16         permute<<< 1, 256 >>>(n/2, data+n/2);
```

```
18     }
19 }
```

Name: n
Type: @parameter int
Value: 2

Value: 2

Endpoint Output

Locals

[illegible]

Page 1 of 1

[illegible]

--

Type here ('Enter' to send): [More](#)


Expression	Value	
1.1.5th July 19		

1. *Journal of the American Medical Association*, 1997; 277: 1033-1036.

Debugging Dynamic Parallelism

```
__global__ void permute(int n, int *data) {  
    __shared__ int smem[256];  
    if (n <= 1)  
        return;  
    smem[threadIdx.x] = data[threadIdx.x];  
    __syncthreads();  
    ...  
}
```

```
__global__ void permute(int n, int *data) {  
    __shared__ int smem[256];  
    if (n <= 1 || threadIdx.x >= n)  
        return;  
    smem[threadIdx.x] = data[threadIdx.x];  
    __syncthreads();  
    ...  
}
```




Debugging is About Understanding

```
smem[threadIdx.x] *= 2; // permute data in
__syncthreads();
// Write back to GMEM since we can't pass
data[threadIdx.x] = smem[threadIdx.x];
__syncthreads();
if (threadIdx.x == 0) {
    permute<<< 1, 256 >>>(n/2, data);
    permute<<< 1, 256 >>>(n/2, data+n/2);
    cudaDeviceSynchronize();
}
```

What actually
happens here?

- Which values are put into `data` and when?
- What's the relationship between `n` and `data`?
- How many kernels are launched?



	Alinea DDT Trial Licence Expires 2013-11-11	Sales
	Alinea MAP Support Expires 2013-11-11	Sales

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K4

CUDA Threads (permute)

Block

0

0

0

Thread

0

0

0

Go

Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

- Application Code
- Sources
- External Code

permute.cu

```
1  #include <stdio.h>
2
3  __global__ void permute(int n, int *data) {
4      __shared__ int smem[256];
5      if (n <= 1 || threadIdx.x >= n)
6          return;
7      smem[threadIdx.x] = data[threadIdx.x];
8      __syncthreads();
9      smem[threadIdx.x] *= 2; // permute data in a trivial way
10     __syncthreads();
11     // Write back to GMEM since we can't pass SMEM to children.
12     data[threadIdx.x] = smem[threadIdx.x];
13     __syncthreads();
14     if (threadIdx.x == 0) {
15         permute<<< 1, 256 >>>(n/2, data);
16         permute<<< 1, 256 >>>(n/2, data+n/2);
17         cudaDeviceSynchronize();
18     }
19 }
20
21 int main(int argc, char** argv) {
```

Locals

Current Line(s)

Current Stack

Current Line(s)

Variable Name	Value
n	256
threadIdx	{x = 0, y = 0, z = 0}
x	0
y	0
z	0
threadIdx.x	0

Input/Output

Breakpoints

Watchpoints

Stacks

Kernel Progress View

Tracepoints

Tracepoint Output

Evaluate

Stacks

Threads	Cuda Threads	Function
1	256	permute (permute.cu:3)
1	256	permute (permute.cu:5)
1	0	main (permute.cu:32)
1	0	cudbgApilnit

Expression

Value

data	
[0]	21
[1]	21
[2]	21
[3]	21
[4]	21
[5]	21
[6]	21
[7]	21
[8]	21
[9]	21
[10]	21

Ready

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K4 5/11

CUDA Threads (permute)

Block

0

0

0

Thread

0

0

0

Go

Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

- Application Code
- /
- Sources
- External Code

permute.cu

```
1  #include <stdio.h>
2
3  __global__ void permute(int n, int *data) {
4      __shared__ int smem[256];
5      if (n <= 1 || threadIdx.x >= n)
6          return;
7      smem[threadIdx.x] = data[threadIdx.x];
8      __syncthreads();
9      smem[threadIdx.x] *= 2; // permute data in a trivial way
10     __syncthreads();
11     // Write back to GMEM since we can't pass SMEM to children.
12     data[threadIdx.x] = smem[threadIdx.x];
13     __syncthreads();
14     if (threadIdx.x == 0) {
15         permute<<< 1, 256 >>>(n/2, data);
16         permute<<< 1, 256 >>>(n/2, data+n/2);
17         cudaDeviceSynchronize();
18     }
19 }
20
21 int main(int argc, char** argv) {
```

Locals

Current Line(s)

Current Stack

Current Line(s)

Variable Name	Value
n	256
threadIdx	{x = 0, y = 0, z = 0}
x	0
y	0
z	0
threadIdx.x	0

Input/Output

Breakpoints

Watchpoints

Stacks

Kernel Progress View

Tracepoints

Tracepoint Output

Evaluate

Tracepoints

	Threads	File	Line	Actual Line	Function	Condition	Start After
<input checked="" type="checkbox"/>	all	permute.cu	15	15	_Z7permuteiPi(int, int * @generic)		0

Expression

Value

data	
[0]	21
[1]	21
[2]	21
[3]	21
[4]	21
[5]	21
[6]	21
[7]	21
[8]	21
[9]	21
[10]	21

Ready

Threads:

1 2 K4 GPU

CUDA Threads (permute)

Block 0 0

Project Files

Search (Ctrl+K)

Application Code

Sources
External Code

permute.cu

#inc

__glo

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

int

Input/Output Breakpoints Watchpoints Stacks

Tracepoints

	Threads	File	Line	Actual Line
<input checked="" type="checkbox"/>	all	permute.cu	15	15

Edit Tracepoint

Location:

☒ Line

File: linea/tools/examples/dynamic_parallelism/permute.cu

Line Number: 15

☐ Function

Applies To:

Thread:

All

Tracepoint Output:

Tracepoint Name: Prefix call site

Variables Logged:

threadIdx.x
n
data[threadIdx.x]

Hit Limits:

Start on the n-th pass:

0

Trigger every n-th pass:

1

Log at most n times:

Never

☐ Condition:

Language:

Auto

OK

Cancel

Locals

Current Line(s)

Current Stack

Current Line(s)

Variable Name	Value
n	256
threadIdx	{x = 0, y = 0, z = 0}
x	0
y	0
z	0
threadIdx.x	0

Type: none selected

ion Value

21

21

21

21

21

21

21

21

21

21

21

Ready

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2

Project Files

Search (Ctrl+K)

- Application Code
- /
- Sources
- External Code

permute.cu

```
26
27     for(i=0;i<256;++i)
28         input[i] = 21;
29
30     cudaMalloc(&data, 256 * sizeof(int));
31     cudaMemcpy(data, input, 256 * sizeof(int), cudaMemcpyHostToDevice);
32     permute<<< 1, 256 >>>(256, data);
33     if (cudaSuccess != cudaGetLastError()) {
34         return 1;
35     }
36     // wait for parent to complete
37     if (cudaSuccess != cudaDeviceSynchronize()) {
38         return 2;
39     }
40     cudaDeviceSynchronize();
41     cudaMemcpy(output, data, 256 * sizeof(int), cudaMemcpyDeviceToHost);
42
43     printf("output[42] = %d\n", output[42]);
44     return 0;
45 }
46
47
```

Locals Current Line(s) Current Stack

Current Line(s)

Variable Name	Value
output	{[0] = 5376, [1] = ...}

Input/Output Breakpoints Watchpoints Stacks Kernel Progress View Tracepoints Tracepoint Output

Tracepoint Output

Tracepoint	Processes	Values logged
Prefix call site	1, process 0	threadIdx.x: 0 n: 256 data[threadIdx.x]: 42
Prefix call site	1, process 0	threadIdx.x: 0 n: 128 data[threadIdx.x]: 84
Prefix call site	1, process 0	threadIdx.x: 0 n: 64 data[threadIdx.x]: 168
Prefix call site	1, process 0	threadIdx.x: 0 n: 32 data[threadIdx.x]: 336
Prefix call site	1, process 0	threadIdx.x: 0 n: 16 data[threadIdx.x]: 672

Only show lines containing:

Evaluate

Expression	Value
data	
output[42]	5376

Tracepoint Output



Tracepoint	Processes	Values logged
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672
Prefix call site	1, process 0	threadIdx.x: — 0 n: — 16 data[threadIdx.x]: — 672



Only show lines containing: 672

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K4

CUDA Threads (permute)

Block

0

0

0

Thread

0

0

0

Go

Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

- Application Code
- Sources
- External Code

permute.cu

```
5 if (n <= 1 || threadIdx.x >= n)
6     return;
7 smem[threadIdx.x] = data[threadIdx.x];
8 __syncthreads();
9 smem[threadIdx.x] *= 2; // permute data in a trivial way
10 __syncthreads();
11 // Write back to GMEM since we can't pass SMEM to children.
12 data[threadIdx.x] = smem[threadIdx.x];
13 __syncthreads();
14 if (threadIdx.x == 0) {
15     permute<<< 1, 256 >>>(n/2, data);
16     permute<<< 1, 256 >>>(n/2, data+n/2);
17     cudaDeviceSynchronize();
18 }
19 }
20
21 int main(int argc, char** argv) {
22     1 Process: process 0
23     int input[256];
24     int output[256];
25     Kernel 4: 31 GPU threads
26     <<<(0,0,0),(1,0,0)>>> ... <<<(0,0,0),(31,0,0)>>> (31 threads)
27     int i;
```

On this line:

```
int main(int argc, char** argv) {
    1 Process: process 0
    int input[256];
    int output[256];
    Kernel 4: 31 GPU threads
    <<<(0,0,0),(1,0,0)>>> ... <<<(0,0,0),(31,0,0)>>> (31 threads)
    int i;
```

Locals

Current Line(s)

Current Stack

Current Line(s)

Variable Name	Value
data	0xb088c0000
n	256
permute	0x400bec <perm

Input/Output

Breakpoints

Watchpoints

Stacks

Kernel Progress View

Tracepoints

Tracepoint Output

Evaluate

Stacks

Threads	Cuda Threads	Function
1	32	permute (permute.cu:3)
1	1	permute (permute.cu:15)
1	31	permute (permute.cu:19)
1	0	main (permute.cu:32)
1	0	cudbgApilnit

Expression

Value

```
data
  output[42] <No symbol "output" in current context.>
```

Focus on current: ☒ Process ☐ Thread ☐ Step Threads Together Step CUDA threads by: Warp (default)

Threads:

1 2 K4 GPU

CUDA Threads (permute)

Block 0 0 0 Thread 0 0 0 Go Grid size: 1x1x1 Block size: 256x1x1

Project Files

Search (Ctrl+K)

Application Code
Sources
External Code

permute.cu

```
5 if (n <= 1 || threadIdx.x >= n)
6     return;
7 smem[threadIdx.x] = data[threadIdx.x];
8 __syncthreads();
9 smem[threadIdx.x] *= 2; // permute data in a trivial way
10 __syncthreads();
11 // Write back to GMEM since we can't pass SMEM to children.
12 data[threadIdx.x] = smem[threadIdx.x];
13 __syncthreads();
14 if (threadIdx.x == 0) {
15     permute<<< 1, 256 >>>(n/2, data);
16     permute<<< 1, 256 >>>(n/2, data+n);
17     cudaDeviceSynchronize();
18 }
19 }
20
21 int main(int argc, char** argv) {
22     int input[256];
23     int output[256];
24     int *data;
25     int i;
```

On this line:

1 Process: process 0

Kernel 4: 1 GPU thread

<<<(0,0,0),(0,0,0)>>> ... <<<(0,0,0),(0,0,0)>>> (1 thread)

Breakpoint for process 0 (will stop at line 19)

Locals

Current Line(s)

Current Stack

Current Line(s)

Variable Name	Value
data	0xb088c0000
n	256
permute	0x400bec <perm


Input/Output Breakpoints Watchpoints Stacks Kernel Progress View Tracepoints Tracepoint Output


Stacks

Threads	Cuda Threads	Function
1	32	permute (permute.cu:3)
1	1	permute (permute.cu:15)
1	31	permute (permute.cu:19)
1	0	main (permute.cu:32)
1	0	cudbgApilnit

Evaluate

Expression	Value
data	
output[42]	<No symbol "output" in current context.>






Alternative sources of inspiration

1. Explain the problem to
a **rubber duck**.

2. Search your **logbooks**:



```
$ grep -ir blas4a logs/*
```

```
segfault-at-4096-procs: Hypothesis: Crash is in blas4a/blas4b
```

```
segfault-at-4096-procs: Observation: rank 9 at blas4a.c:145
```

```
segfault-at-4096-procs: Fix: Switched to ISend in blas4a and
```

```
deadlock-with-openmpi: so the send buffers in blas4a overran.
```

Summary: Inspiration

When you have a sense for what the problem is:

Test it: `$ ddt -offline log.html -trace-at mmult.c:412,rx,ry,rz`

Log it: `$ cat >> logs/short-problem-name`

`Suspect rx is out of bounds in mmult.c:412.`


`Testing with -trace-at mmult.c:412,rx,ry,rz showed...`

Search your logbooks: `$ grep -ri "out of bounds" logs/*`

Talk to a rubber duck.

Tip - set a **time limit** for debugging by inspiration. After 15 minutes, try science.

Debugging by Science



1. Hypothesis
2. Prediction
3. Experiment
4. Observation
5. Conclusion

There is a **reason** for the bug and you **will** find it!

Science: Your logbook

A logbook is at the heart of debugging by science:

hypothesis: cause is in shell_sort()

prediction: At sort.c:6, expect a[] = [11, 4] and size = 2

experiment: -trace-at sort.c:6,a[0],a[1],size

observation: a[] = [11, 14, ?] and size = 3

conclusion: rejected

hypothesis: calling shell_sort with size=3 causes failure

prediction: setting size=2 should make program work

experiment: Set size=2 before call using debugger

observation: As predicted

conclusion: confirmed

allinea


Leaders in parallel software development tools

STAND BACK



**I'M GOING TO TRY
SCIENCE**

Summary: Science





1. Hypothesis
2. Prediction
3. Experiment
4. Observation
5. Conclusion

The method works,
but it may not be as
direct as you'd like!


allinea

Leaders in parallel software development tools

Discipline, Magic, Inspiration, Science



allinea



Leaders in parallel software development tools

Thank-you! Questions?

Discipline, Magic, Inspiration and Science

Mark O'Connor
mark@allinea.com

www.allinea.com